



Biometric Performance:

Reliable, durable and highly accurate fingerprint sensor with latest fingerprint matching algorithm which provides less than 1.5 second user recognition. control panel. Using Weigand-IN port you connect to any card reader for dual factor authentication.



Comunicación:

QUALICA-RD 1000 installs easily on your network having both Ethernet and RS232/485 serial ports. Weigand-OUT port allows connection of reader to or any 3rd party access control panel. Using Weigand-IN port you connect to any card reader for dual factor authentication.



Easy Operation and Management:

Works without computer. Complete setup and programming can be done via keypads and embedded firmware. Audio-Visual Indication for acceptance and rejection of valid/invalid fingerprints, cards and passwords.



Full Access Control Built In:

Relay Outputs for electric lock and alarm. Inputs for door status sensor and request to exit hardware. Supports multiple timezones and personnel groups for programming valid entry zones.



(INDOOR AND OUTDOOR)

Waterproof Enclosure:

IP65 rated waterproof enclosure permits this reader to be used for outdoor applications. The cables and connectors are epoxy sealed at the back of the reader.



Capacity:

Can store up to 2,200 fingerprint templates, 10,000 cards and 30,000 transactions. The data can be backed up to a SD Card and can also be transferred to another reader in the absence of computer connectivity



Options:

Internal Proximity Card or Mifare Card reader allows dual factor authentication for access control.



For Software Developers:


Free SDK and development tools are available for developers/partners who wish to integrate QUALICA-RD 1000 with any application which requires verifying people.

Custom development is also available for OEM partners upon request.



The state of the s

TIME & ATTENDANCE
AND ACCESS CONTROL
BIOMETRIC & RFID READER
QUALICA-RD 1000 WITH IP65
(INDOOR AND OUTDOOR)



CAPACITY:

Fingerprint: 2,200 templates Cards: 10,000 templates Transactions: 30,000 logs

ACCESS CONTROL INTERFACE:

3rd party electric lock, door sensor, exit button, alarm, door bell

POWER:

12V DC, 3A

ENVIRONMENT:

Operating Temperature: 32° to 113° F (0° to 45° C) Operating Humidity: 20% to 80%

DISPLAY:

3.5inch OLED Monochrome Display

COMMUNICATION:

Ethernet, RS 232, RS485, Weigand Input and Output, USB Host

DIMENSIONS:

Height: 7.28 Inches (18.5cm) Length: 2.46 Inches (6.25 cm) Width: 1.63 Inches (4.15 cm) Weight: 0.80lbs (0.36kg)

SUPPORTED CARD FORMATS:

ID Card Mifare Card

